		Page: 1
SAFETY DATA SHEET		Revision Date: 08/02/2018
		Print Date: 9/18/2019
		SDS Number: 000000226882
Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 819195		Version: 3.0

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil

™ Trademark, Valvoline or its subsidiaries, registered in various countries

Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Lubricating oils

<p>Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825)</p> <p>SDS@valvoline.com</p>	<p>Emergency telephone number +1-800-VALVOLINE (+1-800-825-8654)</p> <p>Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825)</p> <p>Product Information 1-800-TEAMVAL (1-800-832-6825)</p>
--	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification


Serious eye damage/eye irritation : Category 2A

Skin sensitisation : Category 1

Short-term (acute) aquatic hazard : Category 2

Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms : 

Signal word : Warning

SAFETY DATA SHEET

Revision Date: 08/02/2018

Print Date: 9/18/2019

SDS Number: 000000226882

Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 819195

Version: 3.0

Hazard statements : H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H401 Toxic to aquatic life.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P264 Wash skin thoroughly after handling.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ eye protection/ face protection.
Response:
 P302 + P352 IF ON SKIN: Wash with plenty of water.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.
Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification
 No information available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
PETROLEUM DISTILLATES	64742-54-7	Asp. Tox. 1; H304	>= 70.00 - < 90.00
ORGANIC COMPOUND	68937-96-2	Skin Corr/Irr 3; H316 Skin Sens. 1B; H317 Aquatic Acute 3; H402 Aquatic Chronic 3; H412	>= 1.00 - < 10.00

SAFETY DATA SHEET

Revision Date: 08/02/2018

Print Date: 9/18/2019

SDS Number: 000000226882


Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 819195

Version: 3.0

Mineral Oil		Asp. Tox. 1; H304	>= 1.00 - < 10.00
React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)		Flam. Liq. 4; H227 Acute Tox. 4; H302 Eye Corr/Irr 1; H318 Skin Sens. 1; H317 Aquatic Acute 2; H401 Aquatic Chronic 2; H411	>= 1.00 - < 10.00
AMINE	112-90-3	Acute Tox. 4; H302 Skin Corr/Irr 1B; H314 Eye Corr/Irr 1; H318 STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0.10 - < 1.00

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.


		Page: 4
SAFETY DATA SHEET		Revision Date: 08/02/2018
		Print Date: 9/18/2019
		SDS Number: 000000226882
Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 819195		Version: 3.0

Do not leave the victim unattended.

- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
acne
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
May cause an allergic skin reaction.
Causes serious eye irritation.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

		Page: 5
SAFETY DATA SHEET		Revision Date: 08/02/2018
		Print Date: 9/18/2019
		SDS Number: 000000226882
Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 819195		Version: 3.0

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO2)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons
acrolein
Aldehydes
formaldehyde
Ketones
Sulphur oxides
Nitrogen oxides (NOx)
hydrogen sulfide
- Specific extinguishing methods : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Product is compatible with standard fire-fighting agents.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

SAFETY DATA SHEET

Revision Date: 08/02/2018

Print Date: 9/18/2019

SDS Number: 000000226882

Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 819195

Version: 3.0

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.
 Do not smoke.
 Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
 Container hazardous when empty.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.
 Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
PETROLEUM DISTILLATES	64742-54-7	CMP (Mist)	5 mg/m3 Mist	AR OEL
		CMP - CPT (Mist)	10 mg/m3 Mist	AR OEL
		TWA (Mist)	5 mg/m3 Mist	PE OEL
		STEL (Mist)	10 mg/m3 Mist	PE OEL
		L-8/40 (Mist)	5 mg/m3 Mist	VE OEL
		LB (Mist)	10 mg/m3 Mist	VE OEL
		CPT (Mist)	5 mg/m3 Mist	PA OEL
		CCT (Mist)	10 mg/m3 Mist	PA OEL
		L-8/40	0.2 mg/m3	VE OEL
		TWA	5 mg/m3	CR OEL
PETROLEUM DISTILLATES	8042-47-5	CMP (Mist)	5 mg/m3	AR OEL

SAFETY DATA SHEET

Revision Date: 08/02/2018

Print Date: 9/18/2019

SDS Number: 000000226882

Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 819195

Version: 3.0

			Mist	
		CMP - CPT (Mist)	10 mg/m3 Mist	AR OEL
		TWA (Mist)	5 mg/m3 Mist	PE OEL
		STEL (Mist)	10 mg/m3 Mist	PE OEL
		L-8/40 (Mist)	5 mg/m3 Mist	VE OEL
		LB (Mist)	10 mg/m3 Mist	VE OEL
		CPT (Mist)	5 mg/m3 Mist	PA OEL
		CCT (Mist)	10 mg/m3 Mist	PA OEL
		L-8/40	0.2 mg/m3	VE OEL
		TWA	5 mg/m3	CR OEL

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:
 Impervious clothing
 Safety shoes
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.
 Discard gloves that show tears, pinholes, or signs of wear.


Hygiene measures : Wash hands before breaks and at the end of workday.
 When using do not eat or drink.
 When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : amber

Odour : oily

		Page: 8
SAFETY DATA SHEET		Revision Date: 08/02/2018
		Print Date: 9/18/2019
		SDS Number: 000000226882
Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 819195		Version: 3.0

Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 199 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: ca. 0.861 g/cm ³
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: ca. 99 mm ² /s (40 °C)
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.

SAFETY DATA SHEET

Revision Date: 08/02/2018

Print Date: 9/18/2019

SDS Number: 000000226882

Version: 3.0

Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 819195

- Possibility of hazardous reactions : Product will not undergo hazardous polymerization.
- Conditions to avoid : None known.
- Incompatible materials : Strong oxidizing agents
- Hazardous decomposition products : Aldehydes
 carbon dioxide and carbon monoxide
 Hydrocarbons
 hydrogen sulfide
 Nitrogen oxides (NOx)
 Sodium oxides
 Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

PETROLEUM DISTILLATES:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg


ORGANIC COMPOUND:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 401
 Assessment: Not classified as acutely toxic by ingestion under GHS.
 Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
 Method: OECD Test Guideline 402
 Assessment: Not classified as acutely toxic by dermal absorption under GHS.
 Remarks: No mortality observed at this dose.

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Acute oral toxicity : LD50 (Rat): ca. 2,000 mg/kg
 Method: OECD Test Guideline 401
 Assessment: The component/mixture is classified as acute oral toxicity, category 4.

		Page: 10
SAFETY DATA SHEET		Revision Date: 08/02/2018
		Print Date: 9/18/2019
		SDS Number: 000000226882
Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 819195		Version: 3.0

AMINE:

Acute oral toxicity : **LD50 (Rat): 1,950 mg/kg**
Remarks: **Information given is based on data obtained from similar substances.**

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

PETROLEUM DISTILLATES:

Result: **Slight, transient irritation**

ORGANIC COMPOUND:

Result: **Mild skin irritation**

AMINE:

Result: **Corrosive after 3 minutes to 1 hour of exposure**

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

PETROLEUM DISTILLATES:

Result: **No eye irritation**

ORGANIC COMPOUND:

Result: **Slight, transient irritation**

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Result: **Corrosive**

AMINE:

Result: **Corrosive**

SAFETY DATA SHEET

Revision Date: 08/02/2018

Print Date: 9/18/2019

SDS Number: 000000226882

Version: 3.0

Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil
™ Trademark, Valvoline or its subsidiaries, registered in various countries
819195

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Components:**ORGANIC COMPOUND:**Test Type: **Maximisation Test**Species: **Guinea pig**Assessment: **The product is a skin sensitiser, sub-category 1B.**Method: **OECD Test Guideline 406**

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Test Type: **Local lymph node assay**Species: **Mouse**Method: **OECD Test Guideline 429**Result: **May cause sensitisation by skin contact.****Germ cell mutagenicity**

Not classified based on available information.

Components:**ORGANIC COMPOUND:**

Genotoxicity in vitro : Test Type: **in vitro assay**
Result: **Positive results were obtained in some in vitro tests.**

Genotoxicity in vivo : Test Type: **Micronucleus test**
Test species: **Mouse**
Cell type: **Bone marrow**
Method: **OECD Test Guideline 474**
Result: **negative**

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.


STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:**AMINE:**Target Organs: **Gastro-intestinal system, Liver, Immune system**

		Page: 12
SAFETY DATA SHEET		Revision Date: 08/02/2018
		Print Date: 9/18/2019
		SDS Number: 000000226882
Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 819195		Version: 3.0

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

PETROLEUM DISTILLATES:

May be fatal if swallowed and enters airways.

Mineral Oil:

May be fatal if swallowed and enters airways.

AMINE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Acute aquatic toxicity Category 3; Harmful to aquatic life.

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

Components:

PETROLEUM DISTILLATES:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l
Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

Revision Date: 08/02/2018

Print Date: 9/18/2019

SDS Number: 000000226882

Version: 3.0

Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 819195

Toxicity to fish (Chronic toxicity) : **NOEC (Fish): 10 mg/l**

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : **NOEC (Aquatic invertebrates): 10 mg/l**

ORGANIC COMPOUND:
 Ecotoxicology Assessment

Short-term (acute) aquatic hazard : **Harmful to aquatic life.**

Long-term (chronic) aquatic hazard : **Harmful to aquatic life with long lasting effects.**

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Toxicity to fish : **LL50 (Oncorhynchus mykiss (rainbow trout)): ca. 24 mg/l**
 Exposure time: 96 h
 Test Type: **static test**
 Test substance: **WAF**
 Method: **OECD Test Guideline 203**

Toxicity to daphnia and other aquatic invertebrates : **EL50 (Daphnia magna (Water flea)): ca. 91.4 mg/l**
 Exposure time: 48 h
 Test Type: **static test**
 Test substance: **WAF**
 Method: **OECD Test Guideline 202**

Toxicity to algae : **ErC50 (Pseudokirchneriella subcapitata (green algae)): 15 mg/l**
 End point: **Growth inhibition**
 Exposure time: 96 h
 Test Type: **static test**
 Method: **OECD Test Guideline 201**

NOEC (Pseudokirchneriella subcapitata (green algae)): 3.3 mg/l
 End point: **Growth inhibition**
 Exposure time: 96 h
 Test Type: **static test**
 Method: **OECD Test Guideline 201**

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : **NOEC (Daphnia magna (Water flea)): 0.12 mg/l**
 Exposure time: 21 d
 End point: **Reproduction Test**
 Test Type: **semi-static test**
 Test substance: **WAF**
 Method: **OECD Test Guideline 211**

SAFETY DATA SHEET

Revision Date: 08/02/2018

Print Date: 9/18/2019

SDS Number: 000000226882

Version: 3.0

Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 819195

Ecotoxicology Assessment

Short-term (acute) aquatic hazard	: Toxic to aquatic life.
Long-term (chronic) aquatic hazard	: Toxic to aquatic life with long lasting effects.

AMINE:

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 0.11 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 0.011 mg/l Exposure time: 48 h
Toxicity to algae	: EC50 (Desmodesmus subspicatus (green algae)): 0.083 mg/l Exposure time: 72 h Remarks: Information given is based on data obtained from similar substances. NOEC (Pseudokirchneriella subcapitata (green algae)): 0.01 mg/l Exposure time: 96 h
M-Factor (Short-term (acute) aquatic hazard)	: 10
M-Factor (Long-term (chronic) aquatic hazard)	: 10

Persistence and degradability

Components:

ORGANIC COMPOUND:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 13 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	---

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 7.4 % Exposure time: 28 d Method: Modified Sturm Test
------------------	---

AMINE:

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 44 % Exposure time: 28 d
------------------	---

No data available

SAFETY DATA SHEET

Revision Date: 08/02/2018

Print Date: 9/18/2019

SDS Number: 000000226882

Version: 3.0

Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 819195

Bioaccumulative potential

Components:

React. prod. of bis(2-methylpentan-2-yl)dithiophosphoricacid + phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched):

Partition coefficient: n-octanol/water : Remarks: **No data available**

AMINE:

Bioaccumulation : Species: **Fish**
 Bioconcentration factor (BCF): **> 500**

Partition coefficient: n-octanol/water : log Pow: **estimated > 4**

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life., Harmful to aquatic life with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water courses or the soil.
 Do not contaminate ponds, waterways or ditches with chemical or used container.
 Send to a licensed waste management company.


Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Empty containers should be taken to an approved waste handling site for recycling or disposal.
 Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

		Page: 16
SAFETY DATA SHEET		Revision Date: 08/02/2018
		Print Date: 9/18/2019
		SDS Number: 000000226882
Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 819195		Version: 3.0

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

UN_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant		no
------------------	--	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Control Order (CCO) : Not applicable

Priority Chemical List (PCL) : Not applicable

Other international regulations

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory


ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : Not in compliance with the inventory

		Page: 17
SAFETY DATA SHEET		Revision Date: 08/02/2018
		Print Date: 9/18/2019
		SDS Number: 000000226882
Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 819195		Version: 3.0

TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information


Revision Date: 08/02/2018

Full text of H-Statements

- H227 Combustible liquid.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H316 Causes mild skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H401 Toxic to aquatic life.
- H402 Harmful to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

		Page: 18
SAFETY DATA SHEET		Revision Date: 08/02/2018
		Print Date: 9/18/2019
		SDS Number: 000000226882
Valvoline Professional Series™ SAE 75W-90 API GL-5 Full Synthetic Gear Oil ™ Trademark, Valvoline or its subsidiaries, registered in various countries 819195		Version: 3.0

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CEATOX

Assistance Center of the Institute of Toxicology
Children's Hospital Clinic, Faculty of Medicine
University of São Paulo.
BR OEL : Occupational Exposure Limit (Brazil)
UY OEL : Occupational Exposure Limit (Uruguay)
PY OEL : Occupational Exposure Limit (Paraguay)